



# Instantor®

Instantor Lever Ball Valves  
Technical Specification



Product Code	771635R, 771635B , 771636R, 771636B, 771637R, 771637B, 771638R, 771638B, 771639R, 771639B.
Description	INSTANTOR® FxF FULL BORE COPPER ALLOY LEVER ACTION BALL VALVES
Size Range	1/4", 3/8" , 1/2", 3/4", 1" FxF with Gland nut and with Red or Blue Coloured PVC Handles
Max Operating Pressure	25 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	100°C.
Min Operating Temperature	-20°C
Material Specification	EN12165 CW617N DW Brass – Plated, EDPM O-rings and with PTFE seals.
To Standard:	Compression Ends to BSP-female. WRAS Cert No.1909344. & KIWA Cert No 1908737. Water fittings Regulation 1999.

**BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!**

Valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids-fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive (2014/68/EU)

T: 01 842 6255 E: sales@Instantor.ie [www.Instantor.ie](http://www.Instantor.ie)

**Sanbra Fyffe Ltd**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

