



Sanbra®

Controls



Motorised Valves with Detachable Heads CxC

- NSAI Approved Irish Instantor® nuts and rings
- CW617N Brass body
- Detachable, Quick Release Head
- Detachable Plug-in Cable
- LED Power indicator
- Imperial and metric sizes
- Five year warranty

CODE	SIZE	NO. OF PORTS	PRICE €
619120	¾"	2 Port	
619122	1"	2 Port	
619124	22mm	2 Port	
619126	28mm	2 Port	
619130	Detachable Head Only		

Technical Specifications

CODE	SIZE	CABLE	FLOW RATE	POWER SUPPLY	FUSE/AUX. SWITCH RATING	MAX. CLOSE OFF PRESSURE	FAIL MODE	WATER TEMP	WARRANTY
619120	¾" 2 Port CxC	1 Metre 5 Core	4.3m³/hr	220-240VAC 50/60Hz 5W	3.0A 250VAC	1.0 bar	Normally closed	5°C to 88°C	5 YEARS
619122	1" 2 Port CxC	1 Metre 5 Core	6.8m³/hr	220-240VAC 50/60Hz 5W	3.0A 250VAC	0.6 bar	Normally closed	5°C to 88°C	5 YEARS
619124	22mm 2 Port CxC	1 Metre 5 Core	4.3m³/hr	220-240VAC 50/60Hz 5W	3.0A 250VAC	1.0 bar	Normally closed	5°C to 88°C	5 YEARS
619126	28mm 2 Port CxC	1 Metre 5 Core	6.8m³/hr	220-240VAC 50/60Hz 5W	3.0A 250VAC	0.6 bar	Normally closed	5°C to 88°C	5 YEARS



Conforms to: EN 60204-1:2006+A1:2009
Low Voltage Directive 2006/95/EC
EN 61000-6-3:2007+A1:2011

EN 61000-6-1:2007
Electromagnetic Compatibility Directive
2004/108/EC



Cylinder Thermostat / Pipe Thermostat

CODE	PACK QTY	PRICE €
771836	10	