



Product Code	SS00001, SS00002, SS00003.			
Description	Range of Solvent Waste Pipe			
Size Range	1 1/4" (O.D. 36mm) 1 1/2" (O.D. 43mm) & 2" (O.D. 56mm) supplied in 4M lengths.			
Colour	White			
Wall Thickness	1 ¼" = 1.8mm, 1 ½" = 1.9mm, 2" = 2.0 mm			
Unit weight:	1.25KG / 1.55 KG / 2.3 KG			
Pack Quantity:	10/10/5			
Max Operating Temperature	70°C flowing medium with restricted short 2 minute duration at 95C			
Min Operating Temperature	-20°C flowing fluid			
Material Specification	PVC-U			
Manufactured to:	BS 4515/ BS 5255			
Pipe support distance (Max)				
	Nom. Dimension	1 1/4"	1 ½"	2"
	Horizontal	0.5m	0.5m	0.5m
	Vertical	1.2m	1.2m	1.2m
Minimum Fall	18mm/m			

For plastic pipe systems the necessary harmonised European Standards (hENs), which allow their CE marking, have not been published yet. This means that it is currently totally illegal to issue a DoP or to apply CE marking to any plastic pipe or fitting unless in very specific cases they are covered by an EAD. This concerns any of the following, end-use applications: - Non-pressure soil and waste discharge, - Underground non-pressure drainage and sewerage, - Buried and above ground conveyance of liquids under pressure, - Hot and cold water distribution.

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie













