



Product Code	SS00001, SS00002, SS00003.												
Description	Range of Solvent Waste Pipe												
Size Range	1 ¼" (O.D. 36mm) 1 ½" (O.D. 43mm) & 2" (O.D. 56mm) supplied in 4M lengths.												
Colour	White												
Wall Thickness	1 ¼" = 1.8mm, 1 ½" = 1.9mm, 2" = 2.0 mm												
Unit weight:	1.25KG / 1.55 KG / 2.3 KG												
Pack Quantity:	10 / 10 / 5												
Max Operating Temperature	70°C flowing medium with restricted short 2 minute duration at 95C												
Min Operating Temperature	-20°C flowing fluid												
Material Specification	PVC-U												
Manufactured to:	BS 5255												
Pipe support distance (Max)	<table border="1"><thead><tr><th>Nom. Dimension</th><th>1 ¼"</th><th>1 ½"</th><th>2"</th></tr></thead><tbody><tr><td>Horizontal</td><td>0.5m</td><td>0.5m</td><td>0.5m</td></tr><tr><td>Vertical</td><td>1.2m</td><td>1.2m</td><td>1.2m</td></tr></tbody></table>	Nom. Dimension	1 ¼"	1 ½"	2"	Horizontal	0.5m	0.5m	0.5m	Vertical	1.2m	1.2m	1.2m
Nom. Dimension	1 ¼"	1 ½"	2"										
Horizontal	0.5m	0.5m	0.5m										
Vertical	1.2m	1.2m	1.2m										
Minimum Fall	18mm/m												

For plastic pipe systems the necessary harmonised European Standards (hENs), which allow their CE marking, have not been published yet. This means that it is currently totally illegal to issue a DoP or to apply CE marking to any plastic pipe or fitting unless in very specific cases they are covered by an EAD. This concerns any of the following, end-use applications: - Non-pressure soil and waste discharge, - Underground non-pressure drainage and sewerage, - Buried and above ground conveyance of liquids under pressure, - Hot and cold water distribution.

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

