



Product Code	SS1001/2/3 Straight Coupler, SS1004/8 straight reducer, SS15001/2/3 Elbow, SS15004/5/6 45° Bend, SS15007/8 Knuckle Elbow, SS18001/2/3 45° Branch Tee, SS18007/8/9 90° Branch Tee, SS19001/2/3 Access Cap, SS19004/5/6 Pipe Clips
Description	Range of Solvent PVC-U fittings
Size Range	1 ¼", 1 ½" & 2"
Colour	White
Wall Thickness	1 ¼" = 1.8mm – 1.95mm, 1 ½" = 1.9mm-2.05mm, 2" = 2.0 -2.15mm
Max Operating Temperature	70°C flowing medium with restricted short 2 minute duration at 95C
Min Operating Temperature	-20°C flowing fluid
Material Specification	PVC-U
Manufactured to:	BS 5255

For plastic pipe systems the necessary harmonised European Standards (hENs), which allow their CE marking, have not been published yet. This means that it is currently illegal to issue a DoP or to apply CE marking to any plastic pipe or fitting unless in very specific cases they are covered by an EAD. This concerns any of the following, end-use applications: - Non-pressure soil and waste discharge, - Underground non-pressure drainage and sewerage, - Buried and above ground conveyance of liquids under pressure, - Hot and cold water distribution.

T: 01 842 6255 E: sales@Instantor.ie [www.Instantor.ie](http://www.Instantor.ie)

**Sanbra Fyffe Ltd**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

