



Product Code	771635R & 771635B / 771636R & 771636B / 771637R & 771637B / 771638R & 771638B/ 771639R & 771639B.
Description	INSTANTOR® FxF FULL BORE COPPER ALLOY LEVER ACTION BALL VALVES F x F with Gland nut and with Red or Blue Coloured PVC Handles, as indicated with the 'R' or 'B' end of product codes,
Size Range	1/4" / 3/8" / 1/2" / 3/4" / 1" /
Max Operating Pressure	25 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	100°C.
Min Operating Temperature	-20°C
Material Specification	EN12165 CW617N Brass – Plated, EDPM O-rings PTFE seals.
Manufactured to:	ISO9001 ISO14001 ISO228 WRAS Cert No.1909344. & KIWA Cert No 1908737. Water fittings Regulation 1999. Reg4UK

**BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!**

Valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids-fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive (2014/68/EU)

T: 01 842 6255 E: sales@Instantor.ie [www.Instantor.ie](http://www.Instantor.ie)

**Sanbra Fyffe Ltd**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TS771635

Issue V.2 February 2024



QUALITY  
IS. EN ISO 9001:2015  
NSAI Certified