



Product Code	771788R, 771788B , 771789R, 771789B, 771790R, 771790B
Description	INSTANTOR® IMPERIAL CxC FULL BORE COPPER ALLOY LEVER ACTION BALL VALVES CxC with Gland nut and with Red or Blue Coloured PVC Handles
Size Range	1/2", 3/4" & 1"
Max Operating Pressure	25 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	85°C. With short term excursions of 95°C (less than 1 hour)
Min Operating Temperature	-20°C
Material Specification	EN12165 CW617N Brass – Plated, EDPM O-rings PTFE seals.
Manufactured to:	ISO9001 ISO14001 I.S.E.N:1254-2:1998 WRAS Cert No. 1904354. & KIWA Cert No. 1904751. Water fittings Regulation 1999 Reg4UK

BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!

Valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids-fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive (2014/68/EU)

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TS771788

Issue V.2 February 2024



QUALITY
IS. EN ISO 9001:2015
NSAI Certified