



Product Code	771861 (1/2" 3Bar), 771862 (3/4" 3 Bar), 771863 (1" 3 Bar) 771864k (1/2" 3 Bar with gauge 0-10 Bar) 771866 (1/2" 6 Bar) 771076: Gauge only 1/4"
Description	Safety Valve/Pressure relief valve (Spring Loaded) with rear port for gauge.
Size Range	1/2" 3 Bar- 1/2" 6 Bar 3/4" 3 Bar & 1" 3 Bar. Female X Female BSP connections.
Min Operating Pressure:	0.4 Bar
Max Operating Pressure:	3 Bar :771861 / 771862 / 771863 / 771864k. 6 Bar valve :771866.
Max Operating Temperature	80°C
Min Operating Temperature	-20°C (Flowing fluid)
Material Specification	Copper Alloy: Brass Body Cap: ABS Springs: Si2Mg Washer: NBR
Manufactured to:	ISO9001:2015 ISO14001:2015 Threads to BSP G-Series: ISO228

BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref: TS771861

Issue V.2 February 2024

