



Product Code	774026DN16 3/4" x 3/4" x 3/4" BSP flat face Tee 774031DN16 3/4" BSP Flat Face Nipple 774036DN16 18mm compression x 3/4" flat face straight 774037DN16 22mm compression x 3/4" flat face straight 774024DN16 18mm Compression x 3/4" flat face Elbow 774035DN16 22mm Compression x 3/4" flat face Elbow 774025DN16 22mm smooth tube spigot x 3/4" BSP flat face
Description	Selection of Brass Solar fittings: Flat faced 3/4" BSP range
Size Range	18mm & 22mm 3/4" BSP flat faces
Max Operating Pressure:	16 Bar
Min Operating Pressure:	0 Bar
Max Operating Temperature	130°C
Min Operating Temperature	-20°C (Flowing Fluid)
Material Specification	Copper Alloy: Brass
Manufactured to:	ISO9001:2015 ISO14001:2015 EN1254 & ISO228 / BSP G-Series Threads EN12165:2016

Products produced from brass are NOT suitable for use underground!!

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TS774026

Issue V.2 February 2024

