



|                           |   |
|---------------------------|---|
| Product Code              | SS1001/2/3 Straight Coupler, SS1004/8 straight reducer, SS15001/2/3 Elbow, SS15004/5/6 45° Bend , SS15007/8 Knuckle Elbow, SS18001/2/3 45° Branch Tee, SS18007/8/9 90° Branch Tee , SS19001/2/3 Access Cap , SS19004/5/6 Pipe Clips |
| Description               | Range of Solvent PVC-U fittings   |
| Size Range                | 1 ¼" , 1 ½" & 2"  |
| Colour                    | White   |
| Wall Thickness            | 1 ¼" = 1.8mm – 2.0mm,<br>1 ½" = 1.9mm-2.05mm,<br>2" = 2.0 -2.15mm   |
| Max Operating Temperature | 70°C flowing medium with restricted short 1 minute duration at 95°C   |
| Min Operating Temperature | -20°C flowing fluid   |
| Material Specification    | PVC-U   |
| Manufactured to:          | BS 5255/EN1329  |

For plastic pipe systems the necessary harmonised European Standards (hENs), which allow their CE marking, have not been published yet. This means that it is currently illegal to issue a DoP or to apply CE marking to any plastic pipe or fitting unless in very specific cases they are covered by an EAD. This concerns any of the following, end-use applications: - Non-pressure soil and waste discharge, - Underground non-pressure drainage and sewerage, - Buried and above ground conveyance of liquids under pressure, - Hot and cold water distribution.

T: 01 842 6255 E: sales@Instantor.ie [www.Instantor.ie](http://www.Instantor.ie)

**Sanbra Fyffe Ltd**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TSSS1001

Issue V.2 February 2024

