



Product Code	700051(1/2" coupler), 700061(3/4" Coupler), 700200(1/2" F.I Coupler), 700210 (1/2" F.I. Coupler) ,700211(15mm F.I. Coupler) Restricted Bore. 700047(15mm coupler), 700048 (15mm Coupler Brass), 700050(15mm coupler), 700053 (22mm Brass Coupler) Full Bore
Description	Isolating (Penny) Valves CxC and CxF in straight and Elbow forms. Brass and Chrome plated.
Size Range	1/2" & 3/4", 15mm & 22mm.
Max Operating Pressure	10 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	65°C
Min Operating Temperature	-20° (Flowing Fluid)
Material Specification	Chrome Plated Copper Alloy - Brass
Manufactured to:	ISO9001 ISO14001 ISEN.1254-2 ISO228.

Products produced from brass are NOT suitable for use underground!

Ball valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids - fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive PED (2014/68/EU)

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TS700051

Issue V.2 February 2024

