



| | |
|---------------------------|---|
| Product Code | CxC: 771851-771852, 771853 & 771940, 771941,771942 FxF: 771841-46 |
| Description | Non Return Valves Spring Loaded |
| Size Range | ½" , ¾" , 1" , 1 ¼" , 1 ½" & 2" , 15mm , 22mm & 28mm |
| Max Operating Pressure | 16 Bar |
| Min Operating Pressure | 0.7 Bar |
| Max Operating Temperature | 90°C |
| Min Operating Temperature | -20°C (Flowing fluid) |
| Material Specification | EN12165 CW617N Brass , ABS & NBR |
| Conforms to Standard: | I.S.E.N.1254-2 and ISO228 G-series Threads (BSP) |

BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!

Valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids-fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive (2014/68/EU)

T: 01 842 6255 E: sales@Instantor.ie www.Instantor.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Doc Ref:TS771851

Issue V.2 February 2024

