CERTIFICATE

Certificate number: 2503764 (1)

Issued *25/03/2025*
Expires *24/03/2030*

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Sanbra Fyffe Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.
Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.
See https://www.kiwa.com/gb/en/about-kiwa/water-products/ or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Sanbra Fyffe Ltd
Instantor Works
Santry Ave
Dublin
DO9 K160
Ireland

kiwa approved KUKreg4 ATS 3

KUKreg4

Product Certificate

Appendix to Certificate number: 2503764

The following products belong to this certificate

PRODUCT DESCRIPTION
Instantor range of copper bodied press fittings with an EPDM ‘O’-ring for use with copper pipe to EN1057. ATS3 – Without Production Surveillance.
MODEL(S) CP310001 Straight Coupler 1/2" X 1/2" CP310002 Straight Coupler 3/4" X 3/4" CP310003 Straight Coupler 1" X 1" CP310021 Straight Reducing Coupler 3/4" x 1/2" CP310031 Straight Reducing Coupler 1" x 1/2" CP310032 Straight Reducing Coupler 1" x 3/4" CP3100S1 Slip Coupler 1/2" CP3100S2 Slip Coupler 3/4" CP3100S3 Slip Coupler 1" CP311001 Male Threaded Straight Coupler M.I 1/2" x Press 1/2" CP311002 Male Threaded Straight Coupler M.I 3/4" x Press 3/4" CP311003 Male Threaded Straight Coupler M.I 1" X Press 1" CP312001 Female Threaded Straight Coupler F.I 1/2" x Press 1/2" CP312002 Female Threaded Straight Coupler F.I 3/4" x Press 3/4" CP312003 Female Threaded Straight Coupler F.I 1" x Press 1" CP315001 90° Elbow 1/2" Press X 1/2" Press CP315002 90° Elbow 3/4" Press X 3/4" Press CP315003 90° Elbow 1" Press x 1" Press CP315021 90° Reducing Elbow 3/4" Press X 1/2" Press CP315031 90° Reducing Elbow 1" Press X 1/2" Press CP315032 90° Reducing Elbow 1" Press X 3/4" Press CP319001 Threaded Wall Plate Elbow F.I 1/2" x 1/2" Press CP319002 Threaded Wall Plate Elbow F.I 3/4" x 3/4" Press CP318001 Equal Tee 1/2" x 1/2" x 1/2" Press CP318002 Equal Tee 3/4" x 3/4" x 3/4" Press CP318003 Equal Tee 1" x 1" x 1" Press CP318112 Reducing Tee 1/2" X 1/2" X 3/4" CP318211 Reducing Tee 3/4" X 1/2" X 1/2" CP318212 Reducing Tee 3/4" X 1/2" X 3/4" CP318221 Reducing Tee 3/4" X 3/4" X 1/2" CP318223 Reducing Tee 3/4" X 3/4" X 1" CP318311 Reducing Tee 1" X 1/2" X 1/2" CP318312 Reducing Tee 1" x 1/2" X 3/4" CP318313 Reducing Tee 1" x 1/2" X 1" CP318321 Reducing Tee 1" x 3/4" X 1/2" CP318322 Reducing Tee 1" x 3/4" X 3/4" CP318323 Reducing Tee 1" x 3/4" X 1" CP318331 Reducing Tee 1" x 1" x 1/2" CP318332 Reducing Tee 1" x 1" x 3/4" CP319021 Push-in Reducer 3/4" Spigot x 1/2" Press CP319031 Push-in Reducer 1" Spigot x 1/2" Press CP319032 Push-in Reducer 1" Spigot x 3/4" Press CP325001 45° Obtuse Street Elbow 1/2" Spigot x 1/2" Press CP325002 45° Obtuse Street Elbow 3/4"Spigot x 3/4" Press CP325003 45° Obtuse Street Elbow 1" Spigot x 1" Press CP335001 90° Street Elbow 1/2" Spigot x 1/2" Press CP335002 90° Street Elbow 3/4" Spigot X 3/4" Press CP335003 90° Street Elbow 1" Spigot X 1" Press

Product Certificate

Appendix to Certificate number: 2503764

CP345001 45° Elbow 1/2" Press x 1/2" Press CP345002 45° Elbow 3/4" Press x 3/4" Press CP345003 45° Elbow 1" Press x 1" Press CP351001 Stop End 1/2" Press CP351002 Stop End 3/4" Press CP351003 Stop End 1" Press
SIZE: See model.
SCOPE: Manufacturer recommended maximum working pressure 16.0 Bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.
MARKING Sanbra Fyffe ‘S’ logo, size, CR and jaw profile ‘V1’ on fitting.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES N/A.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes