



Product Code	771871K , 771872K , 771874K, 771875K, 771877K, 771878K,
Description	Manifolds Male X Female BSP ended with Nut and Insert adapters ('K' code)
Size Range	3/4" BSP (G3/4") X16mm Nut adapter" , 1" BSP (G1") x 16mm Nut adapter – in 2 Port, 3 Port and 4 Port configurations.
Max Operating Pressure	10 Bar @ 20°C , 6 Bar @ 95°C
Min Operating Pressure	0 Bar
Max Operating Temperature	95C Continuous and 110°C short overload of up to a Maximum of 1 Hour
Min Operating Temperature	-5°C (Flowing Fluid)
Material Specification	Manifold -Copper Alloy Brass O-rings – EDPM
Manufactured to:	ISO9001 ISO14001 ISO21003 series. (16mm IP adapters Branch) ISO228

**BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!**

**IE** T: 01 842 6255 E: sales@instantor.ie [www.instantor.ie](http://www.instantor.ie)

**UK** T: 0121 737 2515 E: sales@instantor.co.uk [www.instantor.co.uk](http://www.instantor.co.uk)

### Sanbra Fyffe Ltd - Instantor

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

### Instantor UK

1 Dagger Rd, Lisburn, Northern Ireland, BT28 2TJ

